

F4 BRUTALE 910 S Euro 3	
ENGINE	
Type	Four cylinder, 4 stroke, 16 valve
Timing system	"D.O.H.C", radial valve
Total displacement	909 cm ³ (55.4 cu. in.)
Compression ratio	13:1
Starting	Electric
Bore x stroke	76,0 mm x 50,1 mm (2.99 in. x 1.97 in.)
Max. horse power - r.p.m. (at the crankshaft)	102.2 Kw (139 HP) at 11000 - Lim. 12000 r.p.m.
Max. torque - r.p.m.	96.0 Nm (9.8 Kgm) at 8000 r.p.m.
Cooling system	Cooling with separated liquid and oil radiators
Engine management system	"Weber Marelli" 5SM ignition - injection integrated system; induction discharge electronic ignition; sequential timed "Multipoint" electronic injection
Clutch	Wet, multi - disc
Gear Box	Cassette gearbox; six speed, constant mesh
Primary drive	50/79
Gear ratio	
First gear: Speed*	13/38 105,5 Km/h (65.5 mph) at 12000 r.p.m.
Second gear: Speed*	16/34 145,1 Km/h (90.1 mph) at 12000 r.p.m.
Third gear: Speed*	18/32 173,4 Km/h (107.7 mph) at 12000 r.p.m.
Fourth gear: Speed*	20/30 205,5 Km/h (127.6 mph) at 12000 r.p.m.
Fifth gear: Speed*	22/29 233,9 Km/h (145.2 mph) at 12000 r.p.m.
Sixth gear: Speed*	19/23 262,0 Km/h (162.7 mph) at 12000 r.p.m.
Final velocity ratio	15x43
ELECTRICAL EQUIPMENT	
Voltage	12 V
Alternator	650 W at 5000 r.p.m.
Battery	12 V - 9 Ah
DIMENSIONS AND WEIGHT	
Wheelbase	1410 mm (55.55 in.)
Overall length	2020 mm (79.59 in.)
Overall width	760 mm (29.94 in.)
Saddle height	805 mm (31.72 in.)
Min. ground clearance	135 mm (5.32 in.)
Trail	101,5 mm (4.00 in.)
Dry weight	185 Kg (407.9 lbs)
Fuel tank capacity	19 l (5.02 U.S. gal.) - reserve fuel: 4 l (1.05 U.S. gal.)
PERFORMANCE	
Maximum speed*	262 Km/h (162.7 mph)
FRAME	
Type	CrMo Steel tubular trellis (TIG welded)
Rear swing arm pivot plates: material	Aluminium alloy
FRONT SUSPENSION	
Type	"UPSIDE - DOWN" telescopic hydraulic fork with rebound-compression damping and spring preload adjustment
Rod dia.	50 mm (1.97 in.)
Travel on leg axis	126 mm (4.96 in.)
REAR SUSPENSION	
Type	Progressive, single shock absorber with rebound and compression (High speed / Low speed) damping and spring preload
Single sided swing arm: materiale	Aluminium alloy
Wheel travel	120 mm (4.72 in.)
BRAKE	
Front brake	Double floating disc with Ø 310 mm (Ø 12.2 in.) diameter, with steel braking band and steel flange
Front brake caliper	With 6 pistons - Ø 22,65 mm; Ø 25,4 mm; Ø 30,23 mm (Ø 0.89 in.; Ø 1.00 in.; Ø 1.19 in.)
Rear brake	Single steel disc with Ø 210 mm (Ø 8.27 in.) diameter
Rear brake caliper	With 4 pistons - Ø 25,4 mm (Ø 1.00 in.)
RIM	
Front: Material / size	Aluminium alloy 3.50 " x 17 "
Rear: Material / size	Aluminium alloy 6.00 " x 17 "
TYRES	
Front	120/65 - ZR 17 (56 W) or 120/70 - ZR 17 (56 W-58 W)
Rear	190/50 - ZR 17 (73 W) or 190/55 - ZR 17 (75 W)
FAIRING	
Material	Thermoplastic

* = Top speed attained on closed course.

MV Agusta Motorcycles is committed to the constant improvement of our products. Therefore the information and technical characteristics of the vehicles are subject to change without notice.